

DESKTOP LABEL PRINTER

AD-P30 Wristband printer

Features:

- 2~6inch print speed
- 300 meters large ribbon capacity
- Max.60mm print width
- Thermal transfer and direct thermal printing technology
- Support black mark, 2D barcode printing
- Big media guide, not easily offset for feeding the soft wristband label
- White color design is conform to hospital environment



Specifications

Printer Specifications	Print Method	Thermal Transfer / Direct Thermal
	Print Resolution	203 dpi
	Print Speed	2~6 inch/s (51-152mm/s)
	Print Width	Max. 54mm
	Print Length	Max. 2286mm (90")
	Dot Density	203dots/inch (8dots/mm)
	Dot Size	0.125x0.125mm (1mm=8dots)
	Print Head	30KM
	Interface	USB (USB+Bluetooth, USB+WiFi optional)
	Physical Memory	SDRAM: 8MB, FLASH: 4MB
	Media Sensor	Reflective and Transmissive Sensors (adjustable)
	Command set	Standard TSPL emulation, ZPL emulation optional
	Ribbon Characteristics	Ribbon OD
Ribbon Length		Max.300m
Ribbon Core Size		1 inch (25.4mm)
Ribbon Width		Max.60mm, Min.30mm
Ribbon Rolling Up Method		Outward Rolling
Media Characteristics	Media Roll OD	127mm (5")
	Media Type	Continuous, black mark, gap, punched hole, Fan fold and more labels
	Media Rolling Up Method	Printing side outward rolling
	Media Width	Max.60mm (2.36") Min.20mm (0.78")
	Media Thickness	Max. 0.254mm (10mil) Min. 0.06mm (2.36mil)
	Media Roll Core Size	25.4mm~38mm (1"~1.5")
	Media Gap	Min. 2 mm (0.09")
Label Length	10~2286mm (0.39"~90")	
BarCode/Fonts/ Graphics Symbologies	Enlargement&Rotation	1 ~10 times enlargement in both directions; 0°、 90°、 270°、 360°
	Character Size	Font 0 ~ font 8
	1D Barcode	Code39, Code93, Code128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-13, EAN-14, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, china POS, ITF14
	2D Barcode	QR code
	Graphics Processing	Support BMP/PCX/BAS files
	Editing Software	Nicelabel SE
Operating Characteristics	Power supply	Input: AC 110V/240V Output: DC24V/2.5A, 60W
	Operation Condition	Temperature: 5~45°C(41~104°F), Humidity: 25~85%RH
	Storage Condition	Temperature: -10~50°C(-10~140°F), Humidity: 10%~90%RH
Physical Characteristics	Printer Dimensions	280×160×170(W×D×H)
	Printer Weight	Approx. 1.72KG
Accessories	External Media Holder	Optional



Guangzhou Aide Medical Technology Co., Ltd

T: 86-020-84121751 Web: www.aidemed.cn Email: sales@aidemed.com

Facebook/Instagram/Twitter: @Guangzhou Aide

This data sheet is for informational purposes only. Specifications are subject to change without notice.